

MANDY 16-99



Fountain Pumps

Fountain pumps with three nozzles and a flow control valve are designed for waterfalls, cascades, or streams. They are suitable for building fountains in garden ponds, urban fountains, and other water decorations.

Construction characteristics

- pump housing made of technopolymer
- plastic impeller
- self-cleaning algae filter
- 3 nozzles included
- removable filter cover

Motor

- power supply 230 V
- protection IP68
- speed 2850 rpm
- 10 m power cable

Usage

- liquid type: slightly contaminated water
- max. liquid temperature 35 °C
- max. delivery height depends on the nozzle used

Applications

- indoor fountains
- garden ponds
- water oxygenation
- pumps for filtration systems



Technical parameters

Pump	MANDY 16	MANDY 45	MANDY 70	MANDY 99
Power supply	230 V/50 Hz			
Motor power input	16 W	45 W	70 W	100 W
Max. flow rate (Q max)	1000 l/h	2000 l/h	3000 l/h	5000 l/h
Head (H max)	1.7 m	3 m	3.5 m	4 m
Ingress protection	IP68			
Max. temperature	35 °C			
Cable length	10 m			
Dimension A	70 mm	75 mm	95 mm	
Dimension B	85 mm	110 mm	130 mm	
Dimension L	130 mm	165 mm	195 mm	
Dimension H	560 mm	610 mm	630 mm	
Connection	1/2" - 3/4"	1/2" - 1"		
Nozzles	FT3	FT4		
Weight	1.5 kg	2.1 kg	3 kg	4.5 kg

