

All stainless steel pumps suitable for pumping polluted water from waste pits and excavations. A double seal, two capacitors and a material design make this model for professional use.



## Construction characteristic

---

- pump body of stainless steel AISI 304
- stainless steel impeller AISI 304
- Stainless steel shaft AISI 304
- special double mechanical seal ceramic/carbon, silicon/silicon
- handle and suction body of stainless steel AISI 304

## Motor

---

- degree of protection IP 68
- insulation class B
- single phase version with built-in condenser
- thermal protection in the motor winding
- speed 2850 rpm
- flexicable 10 m H07RNF
- version with float switch

## Usage

---

- type of liquid: slightly polluted water with fixed impurities up to 10 mm
- max. pumped liquid temperature 35°C
- max. height 18 m

## Aplikace

---

- pumping contaminated water and rainwater from pits, pools, cellars, tanks, etc.
- irrigation

<b>Type:</b>	STRATEGY 750
<b>Power input:</b>	750 W
<b>Q max:</b>	12 000 l/h
<b>Head high:</b>	18 m
<b>Voltage:</b>	230 V
<b>Weight:</b>	10 kg
<b>Cable length:</b>	10 m
<b>DNM dimensions:</b>	1,5"
<b>Connection:</b>	1,5"
<b>Max. temperature:</b>	35 °C